

MATERIAL SAFETY DATA SHEET

SECTION 1: Product Identification

TECHNICAL DESCRIPTION: MIL-DTL-24607B, meets Federal Specification MIL-DTL-24607B, dated October 12, 2010
PRODUCT NAME: STIC-KOTE 24607B (all colors)
DESCRIPTION: ENAMEL, INTERIOR, NONFLAMING (DRY), CHLORINATED ALKYD RESIN SEMIGLOSS
SKUs: SK24607B-GL, SK24607B-CN

SECTION 2: Hazardous Ingredients

Chemical	CAS Number	% by Weight	Exposure Limits in Air	
			ACGIH (LTV)	OSHA (PEL)
Titanium Dioxide	13463-67-7	15.0 - 19.0	15 mg/m3 (twa)	15 mg/m3 (twa)
Magnesium Silicate	14807-96-6	5.0 - 8.0	2 mg/m3	20 mppcf
1,2,4-Trimethylbenzene	95-63-6	1.0 - 2.0	25 ppm	25 ppm
Trimethyl benzene	25551-13-7	1.0 -1.5	25 ppm	25 ppm
Paint Thinner	8052-41-3	2.0 - 4.0	100 ppm twa	200 ppm twa (maritime)
Cobalt Drier	136-52-7	0.1 - 0.5	NA	NA
Cumene	98-82-8	< 0.1	50 ppm	50 ppm
Diethyl benzene	25340-17-4	< 0.2	NA	NA

SECTION 3: Physical/Chemical Characteristics

VOC (Volatile Organic Content): Less than 250g/L (2.1 lb./gal.)
VAPOR PRESSURE: 2.0 mmHg at 68°F
BOILING RANGE: 310–390°F (154–197°C) at 760 mmHg

WT/GAL.: 13.0 – 14.0 Lbs.
SPECIFIC GRAVITY: 1.56 – 1.68
VAPOR DENSITY: 4.9 (Air = 1)

SECTION 4: Fire and Explosion Hazard Data

HMIS: H-2* F-2 R-0

US DOT Category: Flammable Liquid
Flashpoint (TCC): 105°F (40°C)

Hazard Class: 3
Shipping Class: 55

ID No.: UN-1263
Packaging Group: III

EXTINGUISHING MEDIA: Use National Fire Protection Association (NFPA) Class B extinguishers (carbon dioxide, dry chemical, or universal aqueous film forming foam) designed to extinguish NFPA class IC flammable liquid fires.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flames. Closed containers may explode when exposed to

extreme heat. Do not apply on hot surfaces. Toxic gases may form when product is contacted by flame or hot surfaces.

SPECIAL FIRE FIGHTING PROCEDURES: Water spray may be ineffective. Water spray may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable. Fire fighters should wear self-contained breathing apparatus.

SECTION 5: Reactivity Data

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Not expected to occur.

INCOMPATIBILITY (Materials and Conditions to Avoid): Avoid contact with strong alkalis, strong mineral acids, or strong oxidizing agents.

SECTION 6: Spill or Leak Procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Provide maximum ventilation. Only personnel equipped with proper respiratory and skin and eye protection should be permitted in the area. Remove all sources of ignition. Take up spilled material with sawdust, vermiculite, or other absorbent material and place into containers for disposal.

WASTE DISPOSAL METHOD: Waste material must be disposed of in accordance with Federal State, Provincial, and Local Environmental Control Regulations. Empty containers should be recycled or disposed of through an approved waste management facility.

SECTION 7: Health Hazard Data

EFFECTS OF OVEREXPOSURE FROM:

INGESTION: Keep person warm, quiet and get immediate medical attention. EYE CONTACT: Causes severe eye irritation. SKIN CONTACT: Causes primary skin irritation. May be harmful if absorbed through the skin. Prolonged or repeated contact may cause an allergic skin reaction. INHALATION: Vapor and spray mist harmful if inhaled. Vapor irritates eyes, nose, and throat. May irritate lungs. Repeated exposure to high vapor concentrations may cause irritation of the respiratory system and permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. CHRONIC OVEREXPOSURE: Avoid long term and repeated contact. This product contains Titanium Dioxide. Animals inhaling massive quantities of Titanium Dioxide dust in a long-term study developed lung tumors. Studies with humans involved in manufacture of this pigment indicate no increased risk of cancer from exposure. Potential for inhalation of Titanium Dioxide dusts from coatings is very limited. Since overexposures are not

expected, there is no significant hazard for man. This product contains a low level of formaldehyde. On the basis of long-term exposure of animals to high levels, NTP, IARC and OSHA associate formaldehyde with an increased risk of cancer. Recent studies with humans show no correlation between exposure to formaldehyde and increased cancer risk.

SIGNS AND SYMPTOMS OF OVEREXPOSURE: Eye watering, headaches, nausea, dizziness, and loss of coordination are indication that solvent levels are too high. Redness, itching, burning sensation and visual disturbances may indicate excessive eye contact. Dryness, itching, cracking, burning, redness, and swelling are conditions associated with excessive skin contact.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:
Not applicable.

SECTION 8: First Aid Procedures

INGESTION: If swallowed, give 2 glasses of water, and do not induce vomiting. Seek immediate medical attention.

EYE CONTACT: In case of eye contact, flush eyes immediately with plenty of water for at least 30 minutes.

SKIN CONTACT: In case of skin contact, flush immediately with plenty of water followed by washing with soap and water.

INHALATION: If affected by inhalation of vapor or spray mist, remove to fresh air. Apply artificial respiration and other supportive measures as required. Call a physician immediately.

OTHER: If ingestion, any type of overexposure or symptoms of overexposure occurs during or following the use of this product, contact a poison control center, emergency room or physician immediately; have Material Safety Data Sheet information available.

SECTION 9: Protection Information

PERSONAL PROTECTIVE EQUIPMENT:

EYE PROTECTION: Wear chemical type splash goggles or full-face shield when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or vapors. **SKIN PROTECTION:** Wear impermeable clothing sufficient to cover exposed skin surfaces constructed of: Nitrile Rubber or Neoprene Rubber. **RESPIRATORY PROTECTION:** Overexposure to vapors may be prevented by ensuring ventilation controls, vapor exhaust or fresh air entry. (NIOSH/MSHA-Approved 9TC-23C) air purifying or air supplied (TC-19C) respirators may also reduce exposure.

Read respirator manufacturer's instructions and literature carefully to determine the type of airborne contaminants against which the respirator is effective and how it is to be properly fitted. **OTHER EQUIPMENT:** Clean or discard contaminated clothing and shoes. **VENTILATION REQUIREMENTS:** Provide general dilution or local exhaust ventilation in volume and pattern to keep the concentration of ingredients listed in Section 2 below the lowest suggested exposure limits, and to remove decomposition products during welding of flame cutting.

SECTION 10: Special Precautions

HANDLING AND STORAGE PRECAUTIONS: Do not store above 120°F. Store large quantities in building designed and protected for storage of NFPA class IC flammable liquids.

OTHER PRECAUTIONS: If this material is part of a multiple component system, read the Material Safety Data Sheet(s) for the

other component or components before blending as the resulting mixture may have the hazards of all of its parts. Containers should be grounded when pouring. Avoid free fall of liquids in excess of a few inches.

SECTION 11: Transportation Information

DOT PROPER SHIPPING NAME: **PAINT**
DOT UN NUMBER: **1263**

DOT HAZARD CLASS: **3**
PACKING GROUP: **III**

OTHER INFORMATION

DISCLAIMER: The material in this Material Safety Data Sheet (MSDS) is, to the best of our knowledge, accurate as of the date issued. However, neither STIC-ADHESIVE nor any of its subsidiaries or agents assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. Compliance with all applicable federal, state, and local laws and regulations remains the responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist. Given the quantity of variables that affect use and application of our products, many of which are within the user's control and unique to each user's knowledge, STIC-ADHESIVE

MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.